

# PRODUCT DATASHEET HALOSTAR ST 10 W 12 V G4

## HALOSTAR® STAR | Low-voltage halogen lamps with pin base



#### Areas of application

- Kitchen lighting
- Mirror lighting
- Lighting for reading
- Entrance lighting
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings

#### **Product benefits**

- Brilliant accent light
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter

#### **Product features**

- Average life: 2,000 h
- 100 % dimmable
- Color rendering index R<sub>a</sub>: 100
- Base: G4, GY6.35


### **TECHNICAL DATA**

#### **Electrical data**

Nominal wattage	10 W
Construction wattage	10.00 W
Nominal voltage	12 V

## Photometrical data

Luminous flux	130 lm
Luminous efficacy	13 lm/W
Light color (designation)	Warm White
Color temperature	2800 К
Color rendering index Ra	100
Light color	1028
UV protection	Yes



## Light technical data

Starting time 0.0 s
---------------------

## **Dimensions & Weight**

Overall length	33.00 mm
Light center length (LCL)	22,0 mm
Diameter	10.00 mm
Product weight	1.17 g

## Lifespan

Nominal lamp life time	2000 h
Number of switching cycles	50000

## Additional product data

Base (standard designation)	G4
Mercury-free	Yes

# Capabilities

Dimmable	Yes
Burning position	Any

### **Certificates & Standards**

Energy efficiency class	G
Energy consumption	10.00 kWh/1000h

### Country-specific categorizations

ILCOS	HSGST/UB-10-12-G4-10/22
Order reference	64415 ST

## Energy labellling regulation data acc EU 2019/2015

Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G4
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	33.00 mm
Height	10.00 mm
Width	10.00 mm
Chromaticity coordinate x	0.452
Chromaticity coordinate y	0.409
Beam angle	SPHERE_360
EPREL ID	714476,714476
Model number	AC35298,AC35298

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321201812	Blister 2	140 mm x 14 mm x 79 mm	24.70 g	0.15 dm³
4008321201829	Shipping box 20	164 mm x 130 mm x 148 mm	202.70 g	3.16 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.