

# Product datasheet

## P CLAS A 75 DIM 10.5 W/827 E27 FR

PARATHOM CLASSIC A DIM | Dimmable LED lamps, classic bulb shape



### Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

### Product family benefits

- Very long lifetime of up to 25,000 h
- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

### Product family features

- LED alternative to conventional lamps
- Good quality of light; color rendering index  $R_a \geq 80$ ; constant chromaticity
- High color consistency: < 6 SDCM
- Dimmable (with many common dimmers, see also [www.osram.com/dim](http://www.osram.com/dim))
- Mercury-free lamps



## Product datasheet

### Technical data

#### Electrical data

Rated wattage	10.50 W
Nominal wattage	10.50 W
Nominal voltage	220...240 V
Operating frequency	50...60 Hz
Power factor $\lambda$	> 0.80
Claimed equiv. conventional lamp power	75 W


#### Photometrical data

Nominal luminous flux	1055 lm
Rated luminous flux	1055 lm
Rated color temperature	2700 K
Color rendering index Ra	$\geq 80$
Light color (designation)	Warm White
Standard deviation of color matching	$\leq 6$ sdcM
Lumen main.fact.at end of nom.life time	0.70

#### Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

#### Dimensions & weight



Overall length	108.0 mm
Diameter	61.5 mm
Outer bulb	A60
Length	108.0 mm

## Product datasheet

### Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

### Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/In development, data preliminary/In preparation/LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance)

### Capabilities

Dimmable	Yes
----------	-----

### Certificates & standards

Energy efficiency class	A+
Energy consumption	11 kWh/1000h

### Country specific categorizations

ILCOS	DRAA/F-10,5/827-220-240-E27-60
Order reference	LEDPCLA75D 10,5

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
--------------	---------------------	------------------------------	--------------------------------------	--------	--------------

## Product datasheet

---

4058075026971	P CLAS A 75 DIM 10.5 W/827 E27 FR	Shipping carton box 10 Pieces Folding carton box	315 mm x 131 mm x 126 mm	5.20 dm <sup>3</sup>	1063.00 g
---------------	--------------------------------------	--	-----------------------------	----------------------	-----------

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### References / Links

For dimming conformity see

- ▶ [www.osram.com/DIM](http://www.osram.com/DIM)

For further products and actual information concerning LED lamps see

- ▶ [www.osram.com/ledlamps](http://www.osram.com/ledlamps)

For Guarantee see

- ▶ [www.osram.com/guarantee](http://www.osram.com/guarantee)

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM GMBH is distribution partner  
of LEDVANCE for Digital Lighting  
Systems and Components

**OSRAM**

OSRAM GmbH  
Marcel-Breuer-Strasse 6  
80807 Munich, Germany