










# Mains voltage halogen lamps

## 3200 K



Product reference	Product number	ANSI	LIF	W		V	t [h]
<b>Single ended</b>							
64743	4050300 <b>227610</b>	FEL	CP/77	1000	G9.5	120	300
64743 HT <sup>1)</sup>	4050300 <b>506531</b>	(FEL)		1000	G9.5	120	300
64576	4050300 <b>014197</b>		P2/17	1000	GX6.35	230	75
64745 <sup>2)</sup>	4050300 <b>213262</b>	FVA	CP/70	1000	GX9.5	230	200
64747 <sup>2)</sup>	4050300 <b>217604</b>	FKJ	CP/71	1000	G22	230	200
93734	4050300 <b>350073</b>	FEP	CP/77	1000	G9.5	240	300
64754	4050300 <b>296746</b>		CP/90	1200	GX9.5	230	200
64756 <sup>2)3)</sup>	4050300 <b>296722</b>		CP/93	1200	G22	230	200

Product reference	Im		d [mm]	l max. [mm]	a [mm]			
64743	27500	any	20	101	60.5	7x18	12	4
64743 HT <sup>1)</sup>	27500	any	20	101	60.3	7x18	12	4
64576	27500	any	24	67.5	38	14x14	25	3
64745 <sup>2)</sup>	26000	s 90	35	110	55	13x15	20	1
64747 <sup>2)</sup>	26000	s 90	35	140	63.5	13x15	20	2
93734	23000	any	20	102	60.3	5.7x27	12	4
64754	30000	s 90	35	125	67	14x16	20	1
64756 <sup>2)3)</sup>	30000	s 90	35	140	63.5	14x16	20	2

1) Only for applications with a high bulb temperature  
 2) Also available for 240 V  
 3) Supplied on request