



UL 61010-1
IEC 61010-2-032
EN 61010-1
EN 61010-2-033
EN 61010-2-032
EN 61326-1



■ UT201



■ UT202



■ UT202A

SPECIFICATIONS



Specifications	Range	Best Accuracy		
		UT201	UT202	UT202A
Model		UT201	UT202	UT202A
AC Current(A)	2A/20A/200A/400A 20A/200A/600A	±(1.5%+5)	±(1.5%+5)	±(1.5%+5)
AC Voltage(V)	2V/20V/200V/600V	±(1.2%+5)	±(1.2%+5)	±(1.2%+5)
DC Voltage(V)	200mV/2V/20V/200V/600V	±(0.8%+1)	±(0.8%+1)	±(0.8%+1)
Resistance(Ω)	200Ω/2kΩ/20kΩ/200kΩ/ 2MΩ/20MΩ	±(1%+2)	±(1%+2)	±(0.8%+3)
Temperature (°C)	-40°C~1000°C		±(1%+3)	
Temperature (°C)	-40°F~1832°F		±(1%+6)	
Features				
Display Count		2000	2000	2000
Auto Range		✓	✓	
Manual Range				✓
Jaw Capacity		28mm	28mm	28mm
Diode		✓	✓	✓
Auto Power Off		✓	✓	
Continuity Buzzer		✓	✓	✓
Low Battery Indication		✓	✓	✓
Data Hold		✓	✓	✓
MAX Mode		✓	✓	✓
MIN Mode				✓
Full Icon Display		✓	✓	
Input Impedance for DCV	Around 10MΩ	✓	✓	✓

GENERAL CHARACTERISTICS

Power	UT201/UT202-1.5V Batteries(R03) × 2, UT202A-9V Battery(6F22)
LCD Size	35.6mm × 18mm
Product Color	Red and Grey
Product Net Weight	220 g
Product Size	210mm × 75.6mm × 30mm
Standard Accessories	UT201/UT202A-Batteries, Test Lead UT202-Battery, Test Lead, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, Carrying Bag, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	540mm × 495mm × 335mm (0.09 CBM Per Standard Carton)
Standard Carton Gross Weight	23 Kg